

EVENT: Chattanooga Green Prix, Spring 2024

DATE: \_\_\_\_\_

TECH INSPECTOR: \_\_\_\_\_

TEAM NAME: \_\_\_\_\_ NUMBER: \_\_\_\_\_

SERIAL NUMBER: \_\_\_\_\_ (If none, assign and stamp the car with the number in front of the roll bar on the right side.)

\_\_\_\_\_ RFID Tag: Installed, Number \_\_\_\_\_

P or F? STOCK CLASS

## ITEM

\_\_\_\_\_ KIT, assembled per Manual, Approved Exceptions

\_\_\_\_\_ MOTOR &amp; BATTERIES: Per Rules

\_\_\_\_\_ BRAKES: Hold to force of 300N

\_\_\_\_\_ STEERING: Minimal play and tires don't contact body

\_\_\_\_\_ BODYWORK: Covers sides and front, approved material, Foam in sides of cockpit, no sharp protrusions

\_\_\_\_\_ WHEELS, TIRES: Wheels as furnished in kit, Tires rated 65 psi or less, All spokes correctly tensioned.

\_\_\_\_\_ MIRRORS: One each side, minimum 6 square inches each

\_\_\_\_\_ NOSE: Forward of bulkhead, 8" foam block, fully deformable nose

\_\_\_\_\_ HORN: Electric, operates by accessible switch

\_\_\_\_\_ BATTERY CUTOFF SWITCH: Operable from in or out of car, marked OFF

\_\_\_\_\_ WIRING: Neat, attached, clear of moving parts

\_\_\_\_\_ NUMBERS: Readable, one each side, one front, including class S, M, C or O on sides, required stickers

\_\_\_\_\_ CONTROLS: Drivers familiar with all,

\_\_\_\_\_ DRIVERS: Advisor assures each driver has experience in car

\_\_\_\_\_ SEAT: Securely attached and padded

\_\_\_\_\_ PERSONAL SAFETY EQUIPMENT: DOT helmet, shield or goggles, head sock, long sleeves, pants, gloves, shoes. Long hair can be tucked into head sock or shirt.

\_\_\_\_\_ ROLL BAR: Installed per Manual, fasteners secure, Tallest driver below line between bars

ALL CLASSES: \_\_\_\_\_ VISIBILITY: All drivers must have forward visibility allowing them to see the pavement no less than 40 feet in front of the car. Booster cushion, if required, should be firmly attached to prevent movement.

## MODIFIED CLASS ONLY

\_\_\_\_\_ KIT: Built per Manual, motor and batteries Stock

\_\_\_\_\_ ALLOWED MODIFICATIONS: Modifications allowed but maintains basic chassis from Kit

\_\_\_\_\_ FRAME LIGHTENING: Frame not lightened beyond what is safe by Tech Inspector or Race Director.

\_\_\_\_\_ WHEELS, TIRES: Wheels as in kit. Wheel sizes match R/L. Tires not labeled in excess of 100 psi.

\_\_\_\_\_ TRACK: Not less than 19.7 inches.

## CUSTOM CLASS ONLY

\_\_\_\_\_ MOTOR, BATTERIES: Same as Stock Class

\_\_\_\_\_ SAFETY ITEMS: Same as Stock Class: brakes, steering, mirrors, nose, horn battery cutoff, wiring, numbers, Driver's safety equipment

\_\_\_\_\_ CHASSIS: Custom chassis, must provide adequate side protection for driver not less than 10" tall, driver and batteries not over 3.9" from ground, Height =&lt; width. Bulkhead at front of chassis, doesn't exceed 110" long or 47" wide

\_\_\_\_\_ WHEELS, TIRES: Wheels 12", 16" or 20". Tires not to exceed 100 psi.

\_\_\_\_\_ SEAT: Secured to chassis. Padded. If driver is reclined to less than 30 degrees from horizontal the seat belt must be 5 point

\_\_\_\_\_ BODYWORK: Allows drivers elbows inside. Provides driver protection at side of cockpit as in Stock Class Rules.